



## E-Z-GO RXV INSTALLATION INSTRUCTIONS



CAUTION: WEAR APPROPRIATE  
EYE PROTECTION!

### Side & Rear Track Installation:

1. Center the long side tracks (with C-Channel facing down) between the top metal supports. The flat part of the tracks will be towards the inside of the car. (See photo #1)
2. Using the screws included, install 4 screws (evenly spaced) through the flat part of the track into the top.  
\*\*Note – The flat part of the track will bend with the curvature of the roof, allowing the screws to be installed.
3. Install rear track by aligning the ends of the track with the edge of the rear canopy strut pocket. Mark and drill outside holes using 5/32" bit. Attach with 2 screws. Mark and drill the center hole and install screw. (See photo # 2)

### Enclosure Installation:

1. Install rear and side enclosure panels by sliding them into the inner channel of the aluminum awning tracks.
2. Remove "sleeves" from enclosure and zip onto front canopy struts. (See photo # 3)
3. Install rear closeout panel by attaching to side panels with hook and loop (plastic bead should align with the bead on the side panels). Tuck bead under seat. Attach closeout panel to seat back using the adhesive backed hook and loop strip.

### Valance Installation:

1. Select the desired valance and slide into the front C-Channel. Snap the valance to the enclosure and place decorative plugs into the ends of the C Channels.

Photo # 1



Photo # 2



Photo # 3

